



HP Server Console Switch Support on AlphaServer Systems

Release Notes

Rev 1.0 July, 2004

This document contains the release notes for the HP server console switch as used on HP AlphaServer systems running the TRU64 UNIX operating system with a PS2 keyboard and mouse.

This guide is intended for anyone who has purchased an HP Server Console Switch (P/N 336044-B21) for use on HP Alpha server systems.

For more information or firmware updates please refer to the following URL:

<http://h18004.www1.hp.com/products/servers/proliantstorage/rack-options/scs/index-kvm.html>

Product Overview

The HP Server Console Switch, 1x8 (8-port) model (P/N 336044-B21), is supported for Alpha systems using PS2 mouse and keyboard with VGA video. This includes support for the PS2 Interface Adapter (P/N 262588-B21) required for operation.

Tru64 Unix Supported

Support is given for systems using the HP Tru64 Unix operating system, version 5.1A or higher. Systems using the HP OpenVMS and Linux operating systems have not been tested and are not supported.

Support for 1x8, 8-port Switch Only

Only the 1x8 (8-port) model (P/N 336044-B21) of the HP Server Console Switch has been tested and is supported for AlphaServer systems.

Minimum Firmware Revisions

The minimum firmware revisions supported (identified as “application” firmware in the on-screen display menu) are as follows:

Switch:	02.00.05
PS2 Interface Adapter:	03.00.01

Support Information

Supported Video Modes

Maximum cable length	Maximum video resolution and monitor frequency supported for the given length of cable			
	1600x1200 @ 75Hz	1280 x 1024 @ 85Hz	1024 x 768 @ 85Hz	800 x 600 @ 85Hz
10ft cable length	Supported	Supported	Supported	Supported
50ft cable length			Supported	Supported
100 ft cable length				Supported

Systems Supported

The following AlphaServer systems have been tested with and are supported for use with the HP Server Console Switch:

AlphaServer DS10, DS15, DS20E, DS25, ES40, ES45, GS80, GS160, GS320

Graphic Cards Supported

The following graphic cards have been tested with and are supported for use on Alpha systems with the HP Server Console Switch:

- ELSA Gloria Synergy (SN-PBXGK-BB)
- 3Dlabs Oxygen VX1 (SN-PBXGF-AB)
- ATI Radeon 7500 (3X-PBXGG-AA/AB)

Monitors Supported

CRT and flat-panel monitors including, but not limited to, HP P1130, HP TFT5600, and TFT5110R are supported.

Keyboard and Mouse Support

Standard PS2 keyboards and mice as supplied with AlphaServer systems, as well as the TFT5600 and 1U Integrated Keyboard and Drawer are supported. For information on supported devices, see the supported options for the system(s) in question at <http://h18002.www1.hp.com/alphaserver/products/options.html>. Note: OpenVMS keyboards are not supported.

Restrictions

Middle Mouse Button Not Supported

The middle mouse button (button 2) on a three-button mouse does not function and is not supported on Alpha systems. This restriction may be removed in the future by a firmware update.

USB Keyboard/Mouse Not Supported

The USB interface adapter is not supported on AlphaServer systems. For systems that require USB keyboard and mouse, such as AlphaServer ES47, ES80, and GS1280, use the switch supported on those systems, 3X-KVMUS-AA.

Energy-Mode Screensaver and HP TFT5600, HP TFT5110R

Use of the energy-saving mode screensaver incorporated into the HP Server Console Switch is not supported when a TFT5600 or TFT5110R rack-mount display is connected to the HP Server Console Switch. The energy-saving mode of the screensaver causes undesirable behavior in these displays.

Cascade Configurations with Other KVMs and Expansion Module

While cascade (tiered) configurations are supported, the HP Server Console Switch may only be cascaded with another HP Server Console Switch for Alpha system applications. Cascaded configurations with any other model of HP or Compaq console switch are not supported.

Only one level of cascading is supported.

The HP Server Console Switch Expansion Module (P/N 262589-B21) is not supported.

Hot-Plugging the Interface Adapter into the Server

While the HP Server Console Switch user guide allows hot-plugging the keyboard and mouse connectors of the PS2 interface adapter into the server system, for Alpha systems it is recommended that the system be powered down while the PS2 keyboard and mouse are being connected or disconnected.

Configuration Notes

Cabling

On AlphaServer GS80, GS160, and GS320 systems it may be necessary to use an extension cable to reach the video connector from the interface adapter because of the relative position of the keyboard/mouse and video connectors.

Screen Saver when Menu Delay > 0

The HP Server Console Switch incorporates a feature that can delay the appearance of the main on-screen-display menu when the user presses the [Prt Scrn] key (the default setting is "0", or no delay). If the menu delay is set to a value greater than zero, and the screen saver activates while the on-screen-display menu is on the screen, 'waking up' the switch will not show the on-screen-display menu. However the menu is still active and the switch is intercepting all keystrokes and mouse activity, so that the selected system will appear to not be responding. If this happens, press the [esc] key once to exit the on-screen-display menu and return control to the server. The switch will continue to operate normally.